

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/13/2026 |
| 3.4 | 05/13/2026 | 150000093410 | Date of first issue: 09/06/2016 |

SECTION 1. IDENTIFICATION

Product name : Skydrol® PE-5

Product code : 34103-00, P3410305, P3410304, P3410302, P3410301, P3410306, P3410314, P3410313, P3410312, P3410303, P3410311, P3410309, E3410301

Manufacturer or supplier's details

Company name of supplier : Eastman Chemical Company

Address : 200 South Wilcox Drive
Kingsport TN 37660-5147

Telephone : (423) 229-2000

Emergency telephone : CHEMTREC: +1-800-424-9300, +1-703-527-3887 CCN7321

Recommended use of the chemical and restrictions on use

Recommended use : Hydraulic fluids

Restrictions on use : The Environmental Protection Agency prohibits processing and distribution of this chemical/product for any use other than: (1) In hydraulic fluids either for the aviation industry or to meet military specifications for safety and performance where no alternative chemical is available that meets U.S. Department of Defense specification requirements, (2) lubricants and greases, (3) new or replacement parts for motor and aerospace vehicles, (4) as an intermediate in the manufacture of cyanoacrylate glue, (5) in specialised engine air filters for locomotive and marine applications, and (6) in adhesives and sealants before January 6, 2025, after which use in adhesives and sealants is prohibited. In addition, all persons are prohibited from releasing PIP (3:1) to water during manufacturing, processing and distribution in commerce, and must follow all existing regulations and best practices to prevent the release of PIP (3:1) to water during the commercial use of PIP (3:1).

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Acute toxicity (Oral) : Category 4

Skin irritation : Category 2

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001


Version 3.4 Revision Date: 05/13/2026 SDS Number: 150000093410 Date of last issue: 05/13/2026
Date of first issue: 09/06/2016

Carcinogenicity : Category 2
Reproductive toxicity (Oral) : Category 2
Specific target organ toxicity : Category 2 (Adrenal gland)
- repeated exposure

Other hazards

None known.

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H302 Harmful if swallowed.
H315 Causes skin irritation.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child if swallowed.
H373 May cause damage to organs (Adrenal gland) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/13/2026 |
| 3.4 | 05/13/2026 | 150000093410 | Date of first issue: 09/06/2016 |

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components

| Chemical name | CAS No./Unique ID | Concentration (% w/w) | Trade secret |
|--|-------------------|-----------------------|--------------|
| Tributyl phosphate | 126-73-8* | $\geq 50 - \leq 70$ | - |
| Triisobutyl phosphate | 126-71-6* | $\geq 10 - \leq 20$ | - |
| Phenol, isopropylated, phosphate (3:1) | 68937-41-7* | $\geq 5 - \leq 10$ | - |
| 7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester | 62256-00-2* | $\geq 5 - \leq 10$ | - |
| triphenylphosphate | 115-86-6* | $\geq 1 - \leq 5$ | - |

* Indicates that the identifier is a CAS No.

Eastman is committed to the safety, health and environment of our employees, our customers, and the communities we operate within. As part of this commitment, Eastman's Safety Data Sheets (SDS) are prepared in accordance with all applicable national and local regulations. The compositions of our documents reflect these requirements which include, but are not limited to, requirements under the Globally Harmonized System of Classification and Labeling (GHS). These compositions commonly involve the use of ranges versus specific analytical values. If you require a composition that is more specific, please refer to the Certificate of Analysis, sales specification, or contact your Customer Service Representative.

SECTION 4. FIRST AID MEASURES

- If inhaled : Move to fresh air.
Call a physician or poison control center immediately.
- In case of skin contact : Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Wash contaminated clothing before re-use.
Get medical attention.
Thoroughly clean shoes before reuse.
- In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- If swallowed : Seek medical advice.
- Most important symptoms and effects, both acute and delayed : Harmful if swallowed.
Causes skin irritation.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child if swallowed.

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/13/2026 |
| 3.4 | 05/13/2026 | 150000093410 | Date of first issue: 09/06/2016 |

May cause damage to organs through prolonged or repeated exposure.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO2)
Dry chemical
Water spray

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

Specific hazards during fire fighting : None known.

Hazardous combustion products : Carbon monoxide
Carbon dioxide (CO2)
oxides of phosphorus

Further information : None known.

Special protective equipment for fire-fighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Wear appropriate personal protective equipment.
Avoid breathing mist or vapors.
Local authorities should be advised if significant spillages cannot be contained.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
Clear up spills immediately and dispose of waste safely.
Avoid release to the environment.

Methods and materials for containment and cleaning up : Prevent runoff from entering drains, sewers, or streams.
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against : None known.

SAFETY DATA SHEET



according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

Version 3.4 Revision Date: 05/13/2026 SDS Number: 150000093410 Date of last issue: 05/13/2026
Date of first issue: 09/06/2016

fire and explosion

Advice on safe handling : Avoid inhalation of vapor or mist.
Do not get on skin or clothing.
Avoid contact with skin, eyes and clothing.
Do not swallow.
Ensure adequate ventilation.
Wash thoroughly after handling.

Conditions for safe storage : Keep tightly closed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|--------------------|----------|------------------------------------|--|-----------|
| Tributyl phosphate | 126-73-8 | TWA (Inhalable fraction and vapor) | 5 mg/m ³ | ACGIH |
| | | TWA | 0.2 ppm 2.5 mg/m ³ | NIOSH REL |
| | | TWA | 5 mg/m ³ | OSHA Z-1 |
| | | TWA | 0.2 ppm 2.5 mg/m ³ | OSHA P0 |
| triphenylphosphate | 115-86-6 | TWA | 3 mg/m ³ | ACGIH |
| | | TWA | 3 mg/m ³ | NIOSH REL |
| | | TWA | 3 mg/m ³ | OSHA Z-1 |
| | | TWA | 3 mg/m ³ | OSHA P0 |

Engineering measures : Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Remarks : Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. After contamination with product change the gloves immediately and dispose of them according to relevant national and local regulations. Wear suitable gloves.

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/13/2026 |
| 3.4 | 05/13/2026 | 150000093410 | Date of first issue: 09/06/2016 |

Eye protection : Wear safety glasses with side shields (or goggles).

Skin and body protection : Wear suitable protective clothing.

Protective measures : Remove respiratory and skin/eye protection only after vapors have been cleared from the area.
Ensure that eye flushing systems and safety showers are located close to the working place.
Use personal protective equipment as required.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : oily

Color : purple

Odor : odorless

Odor Threshold : not determined

pH : not determined

Melting point/ range : < -80 °F / -62 °C

Boiling point/boiling range : not determined

Flash point : 340 °F / 171 °C
Method: Cleveland open cup

Evaporation rate : not determined

Flammability (solid, gas) : Not applicable

Upper explosion limit / Upper flammability limit : not determined

Lower explosion limit / Lower flammability limit : not determined

Vapor pressure : 0.4 hPa (77 °F / 25 °C)

Relative vapor density : not determined

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/13/2026 |
| 3.4 | 05/13/2026 | 150000093410 | Date of first issue: 09/06/2016 |

| | | |
|--|---|---------------------------------------|
| Relative density | : | 0.9956 (77 °F / 25 °C) |
| Density | : | 995 kg/m3 (77 °F / 25 °C) |
| Partition coefficient: n-octanol/water | : | No data available |
| Autoignition temperature | : | 795 °F / 424 °C Method: ASTM D2155 |
| Decomposition temperature | : | not determined |
| Viscosity | | |
| Viscosity, dynamic | : | not determined |
| Viscosity, kinematic | : | 9.02 - 10.02 mm2/s (100 °F / 38 °C) |
| Explosive properties | : | Not classified |
| Oxidizing properties | : | Not classified |

SECTION 10. STABILITY AND REACTIVITY

| | | |
|------------------------------------|---|---|
| Reactivity | : | None reasonably foreseeable. |
| Chemical stability | : | Stable under normal conditions. |
| Possibility of hazardous reactions | : | Stable |
| Conditions to avoid | : | None known. |
| Incompatible materials | : | Strong oxidizing agents |
| Hazardous decomposition products | : | Carbon dioxide (CO2) Carbon monoxide |

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed.

Product:

| | | |
|---------------------------|---|---|
| Acute oral toxicity | : | LD50: 1,600 mg/kg Remarks: Harmful if swallowed. |
| Acute inhalation toxicity | : | Remarks: No significant adverse effects were reported |
| Acute dermal toxicity | : | Remarks: No data available |

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

Version 3.4 Revision Date: 05/13/2026 SDS Number: 150000093410 Date of last issue: 05/13/2026
Date of first issue: 09/06/2016

Components:

Tributyl phosphate:

- Acute oral toxicity : LD50 Oral (Rat, male and female): 1,553 mg/kg
Assessment: Harmful if swallowed.
- LD50 Oral (Rat, male and female): 1,400 mg/kg
- Acute inhalation toxicity : LC50 (Rat, male and female): > 4.242 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 3,100 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Triisobutyl phosphate:

- Acute inhalation toxicity : LC50 (Rat): > 5.14 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Phenol, isopropylated, phosphate (3:1):

- Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
- Acute inhalation toxicity : LC50 (Rat): > 200 mg/m³
Exposure time: 1 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 10,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

- Acute oral toxicity : LD50 Oral (Rat, male and female): 4,470 mg/kg
- Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 7,940 mg/kg

triphenylphosphate:

- Acute oral toxicity : LD50 Oral (Rat, male): > 6,400 mg/kg

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/13/2026 |
| 3.4 | 05/13/2026 | 150000093410 | Date of first issue: 09/06/2016 |

Acute dermal toxicity : LD50 Dermal (Guinea pig, male): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : Causes skin irritation.

Components:

Tributyl phosphate:

Species : Rabbit
Exposure time : 4 h
Assessment : Causes skin irritation.
Result : irritating

Triisobutyl phosphate:

Species : Rabbit
Exposure time : 4 h
Result : Mild skin irritation

Phenol, isopropylated, phosphate (3:1):

Species : Rabbit
Assessment : Not classified

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

Species : Rabbit
Exposure time : 24 h
Assessment : Not classified as hazardous.
Result : slight to moderate irritation

triphenylphosphate:

Species : Guinea pig
Remarks : Non-irritating to the skin.

Serious eye damage/eye irritation

Not classified due to lack of data.

Components:

Tributyl phosphate:

Species : Rabbit
Result : slight irritation
Exposure time : 24 h
Assessment : Not classified

Triisobutyl phosphate:

Species : Rabbit

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/13/2026 |
| 3.4 | 05/13/2026 | 150000093410 | Date of first issue: 09/06/2016 |

Result : slight
Assessment : Not classified

Phenol, isopropylated, phosphate (3:1):

Species : Rabbit
Result : none
Assessment : Not classified

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

Species : Rabbit
Result : slight irritation
Exposure time : 24 h
Assessment : Not classified

triphenylphosphate:

Species : Rabbit
Result : slight

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Not classified due to lack of data.

Product:

Test Type : OECD 429: LLNA
Species : Mouse
Assessment : Not classified
Result : Not a skin sensitizer.
Remarks : Read-across from a similar material

Components:

Tributyl phosphate:

Test Type : Skin Sensitization
Species : Guinea pig
Assessment : Not classified
Result : Does not cause skin sensitization.

Test Type : Skin Sensitization
Species : Humans
Assessment : Not classified
Result : Does not cause skin sensitization.

Triisobutyl phosphate:

Test Type : OECD 406: Guinea pig sensitization
Species : Guinea pig
Method : OECD 406: Guinea pig sensitization
Result : May cause sensitization by skin contact.

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/13/2026 |
| 3.4 | 05/13/2026 | 150000093410 | Date of first issue: 09/06/2016 |

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

Test Type : Skin Sensitization
Species : Guinea pig
Result : May cause sensitization by skin contact.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

Tributyl phosphate:

Genotoxicity in vitro : Test Type: Mutagenicity - Bacterial
Metabolic activation: +/- activation
Method: Bacterial Reverse Mutation Assay
Result: negative

Test Type: Mutagenicity - Mammalian
Metabolic activation: +/- activation
Method: In vitro Mammalian Chromosome Aberration Test
Result: equivocal

Genotoxicity in vivo : Species: Rat (male and female)
Application Route: oral: gavage
Method: Mammalian Bone Marrow Chromosome Aberration Test
Result: negative

Triisobutyl phosphate:

Genotoxicity in vitro : Test Type: Salmonella typhimurium assay (Ames test)
Metabolic activation: +/- activation
Method: Bacterial Reverse Mutation Assay
Result: negative

Genotoxicity in vivo : Result: negative

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

Genotoxicity in vitro : Test Type: Salmonella typhimurium assay (Ames test)
Metabolic activation: +/- activation
Method: Bacterial Reverse Mutation Assay
Result: negative

Test Type: Mutagenicity - Mammalian
Metabolic activation: +/- activation
Method: In vitro Mammalian Chromosome Aberration Test
Result: equivocal

Test Type: Mutagenicity - Mammalian
Metabolic activation: +/- activation
Method: In vitro Mammalian Cell Gene Mutation Test
Result: negative

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/13/2026 |
| 3.4 | 05/13/2026 | 150000093410 | Date of first issue: 09/06/2016 |

Genotoxicity in vivo : Species: Rat (male and female)
Application Route: intraperitoneal injection
Method: Mammalian Bone Marrow Chromosome Aberration Test
Result: equivocal

Carcinogenicity

Suspected of causing cancer.

Product:

Remarks : This information is not available.

Components:

Tributyl phosphate:

Species : Rat, male and female
Application Route : Ingestion
Method : EPA OTS 798.3300
Remarks : Limited evidence of a carcinogenic effect.
May cause cancer.

IARC **Group 2B: Possibly carcinogenic to humans**

n-butyl methacrylate 97-88-1

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging fertility or the unborn child if swallowed.

Product:

Effects on fertility : Remarks: No data available

Components:

Phenol, isopropylated, phosphate (3:1):

Effects on fertility : Species: Rat, male and female
Application Route: Oral
General Toxicity Parent: NOAEL: 25 milligram per kilogram
Remarks: Suspected of damaging fertility or the unborn child.

triphenylphosphate:

Reproductive toxicity - Assessment : Based on available data, the classification criteria are not met.

STOT-single exposure

Not classified due to lack of data.

SAFETY DATA SHEET



according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

Version 3.4 Revision Date: 05/13/2026 SDS Number: 150000093410 Date of last issue: 05/13/2026
Date of first issue: 09/06/2016

Product:

Remarks : No data available

Components:

Tributyl phosphate:

Assessment : Based on available data, the classification criteria are not met.

Triisobutyl phosphate:

Assessment : Not classified

Phenol, isopropylated, phosphate (3:1):

Remarks : Not classified due to data which are conclusive although insufficient for classification.

STOT-repeated exposure

May cause damage to organs (Adrenal gland) through prolonged or repeated exposure.

Product:

Remarks : No data available

Components:

Tributyl phosphate:

Assessment : Based on available data, the classification criteria are not met.

Triisobutyl phosphate:

Assessment : Not classified

Phenol, isopropylated, phosphate (3:1):

Assessment : May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

Tributyl phosphate:

Species : Mouse, male and female
: 75 mg/kg
Application Route : in feed
Exposure time : 90 days

Triisobutyl phosphate:

Species : Rat, male
: 68.4 mg/kg
Application Route : Oral Study
Exposure time : 90 days

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/13/2026 |
| 3.4 | 05/13/2026 | 150000093410 | Date of first issue: 09/06/2016 |

Aspiration toxicity

Based on available data, the classification criteria are not met.

Product:

No aspiration toxicity classification

Components:

Triisobutyl phosphate:

Not classified

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

Not applicable

Experience with human exposure

Product:

| | | |
|--------------|---|--|
| Inhalation | : | Remarks: Causes damage to organs through prolonged or repeated exposure. |
| Skin contact | : | Remarks: Causes skin irritation. |
| Eye contact | : | Remarks: None known. |
| Ingestion | : | Remarks: Harmful if swallowed. |

Further information

Product:

Remarks : None known.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Tributyl phosphate:

| | | |
|---|---|---|
| Toxicity to fish | : | LC50 (Oncorhynchus mykiss (rainbow trout)): 4.2 mg/l Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 1.8 mg/l Exposure time: 48 h |
| Toxicity to algae/aquatic plants | : | EC50 (Desmodesmus subspicatus (green algae)): 1.1 mg/l Exposure time: 72 h |
| Toxicity to fish (Chronic toxicity) | : | NOEC (Oncorhynchus mykiss (rainbow trout)): 0.82 mg/l Exposure time: 95 d |

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/13/2026 |
| 3.4 | 05/13/2026 | 150000093410 | Date of first issue: 09/06/2016 |

1.7 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1.3 mg/l
Exposure time: 21 d

Triisobutyl phosphate:

Toxicity to fish : EC50 (Danio rerio (zebra fish)): > 12.6 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 24 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (algae)): 14.3 mg/l
Exposure time: 72 h

EC10 (Pseudokirchneriella subcapitata (algae)): 10.4 mg/l
Exposure time: 72 h

Phenol, isopropylated, phosphate (3:1):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.36 mg/l
Exposure time: 96 h

LC50 (Cyprinodon variegatus (sheepshead minnow)): > 1.3 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 1 mg/l
Exposure time: 48 h

LC50 (Mysidopsis bahia (opossum shrimp)): > 1 mg/l

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): 0.25 - 2.5 mg/l
Exposure time: 72 h
Test Type: Alga, Growth Inhibition Test

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (algae)): 2.6 mg/l
Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (algae)): 0.11 mg/l
Exposure time: 72 h

triphenylphosphate:

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/13/2026 |
| 3.4 | 05/13/2026 | 150000093410 | Date of first issue: 09/06/2016 |

| | | |
|--|---|--|
| Toxicity to fish | : | LC50 (Oncorhynchus mykiss (rainbow trout)): 0.4 mg/l Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | LC50 (Americamysis): > 0.18 - < 0.32 mg/l Exposure time: 96 h |
| Toxicity to algae/aquatic plants | : | NOEC (Pseudokirchneriella subcapitata (algae)): 0.25 mg/l Exposure time: 72 h |
| Toxicity to fish (Chronic toxicity) | : | EC10 (Oncorhynchus mykiss (rainbow trout)): 0.037 mg/l Exposure time: 30 d |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOEC (Daphnia magna (Water flea)): 0.254 mg/l Exposure time: 21 d |

Persistence and degradability

Components:

Tributyl phosphate:

Biodegradability : Result: Readily biodegradable.

Triisobutyl phosphate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 - 80 %
Exposure time: 28 d
Method: Ready Biodegradability: CO2 Evolution Test

Phenol, isopropylated, phosphate (3:1):

Biodegradability : Remarks: Not readily biodegradable.

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

Biodegradability : Concentration: 100 mg/l
Result: Readily biodegradable.
Method: Ready Biodegradability: Modified MITI Test (I)
Remarks: Readily biodegradable

triphenylphosphate:

Biodegradability : Result: Readily biodegradable.

Bioaccumulative potential

Components:

Tributyl phosphate:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 20
Exposure time: 56 d
Method: OECD Test Guideline 305

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/13/2026 |
| 3.4 | 05/13/2026 | 150000093410 | Date of first issue: 09/06/2016 |

Bioconcentration factor (BCF): 35
Exposure time: 38 d

Partition coefficient: n-octanol/water : Pow: 10,100

Triisobutyl phosphate:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 3.72

Phenol, isopropylated, phosphate (3:1):

Bioaccumulation : Remarks: Potential bioaccumulation

triphenylphosphate:

Partition coefficient: n-octanol/water : log Pow: 4.63

Mobility in soil

Components:

Phenol, isopropylated, phosphate (3:1):

Distribution among environmental compartments : log Koc: 3.43 - 3.93

Other adverse effects

No data available

Endocrine disrupting properties

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : This product meets the criteria for a synthetic used oil under the U.S. EPA Standards for the Management of Used Oil (40 CFR 279). Those standards govern recycling and disposal in lieu of 40 CFR 260 -272 of the Federal hazardous waste program in states that have adopted these used oil regulations. Consult your attorney or appropriate regulatory official to be sure these standards have been adopted in your state. Recycle or burn in accordance with the applicable standards.
Dispose of in accordance with local regulations.

Must be incinerated.
Minimum incineration temperature necessary to ensure complete destruction of waste:
incineration above 900 C is necessary.

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/13/2026 |
| 3.4 | 05/13/2026 | 150000093410 | Date of first issue: 09/06/2016 |

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s. (triphenyl phosphate)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964
Remarks : This product can be subject to exemptions when packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids, or having a net mass of 5 kg or less for solids.

IMDG-Code

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (triphenyl phosphate)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes
Remarks : This product can be subject to exemptions when packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids, or having a net mass of 5 kg or less for solids.

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s. (triphenyl phosphate)
Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171
Marine pollutant : yes(triphenyl phosphate)

SAFETY DATA SHEET



according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/13/2026 |
| 3.4 | 05/13/2026 | 150000093410 | Date of first issue: 09/06/2016 |

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Acute toxicity (any route of exposure)
Carcinogenicity
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Skin corrosion or irritation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

The ingredients of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIC : On the inventory, or in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZloC : On the inventory, or in compliance with the inventory

TECI : Not in compliance with the inventory

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/13/2026 |
| 3.4 | 05/13/2026 | 150000093410 | Date of first issue: 09/06/2016 |

TSCA list

The following substance(s) is/are subject to a Significant New Use Rule:

| | | |
|---|------------|--|
| Potassium decafluoro(pentafluoroethyl)cyclohexanesulphonate | 67584-42-3 | See 40 CFR § 721.9582; [67 FR 72863, Dec. 9, 2002, as amended at 72 FR 57229, Oct. 9, 2007, and amended at 78 FR 62450, Oct. 22, 2013]; Final Rule See 40 CFR § 721.9582; Proposed Rule |
|---|------------|--|

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:

Phenol, isopropylated, phosphate (3:1) 68937-41-7

The following substance(s) is/are subject to TSCA - 6 Risk Management Rules List of Chemicals:

Phenol, isopropylated, phosphate (3:1) 68937-41-7

The Environmental Protection Agency prohibits processing and distribution of this chemical/product for any use other than: (1) In hydraulic fluids either for the aviation industry or to meet military specifications for safety and performance where no alternative chemical is available that meets U.S. Department of Defense specification requirements, (2) lubricants and greases, (3) new or replacement parts for motor and aerospace vehicles, (4) as an intermediate in the manufacture of cyanoacrylate glue, (5) in specialised engine air filters for locomotive and marine applications, and (6) in adhesives and sealants before January 6, 2025, after which use in adhesives and sealants is prohibited. In addition, all persons are prohibited from releasing PIP (3:1) to water during manufacturing, processing and distribution in commerce, and must follow all existing regulations and best practices to prevent the release of PIP (3:1) to water during the commercial use of PIP (3:1).

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001


Version
3.4

Revision Date:
05/13/2026

SDS Number:
150000093410

Date of last issue: 05/13/2026
Date of first issue: 09/06/2016

NFPA 704:



HMIS® IV / CED:

| | | |
|-----------------|---|---|
| HEALTH | * | 2 |
| FLAMMABILITY | | 1 |
| PHYSICAL HAZARD | | 0 |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

| | | |
|-----------------|---|---|
| ACGIH | : | USA. ACGIH Threshold Limit Values (TLV) |
| NIOSH REL | : | USA. NIOSH Recommended Exposure Limits |
| OSHA P0 | : | USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values) |
| OSHA Z-1 | : | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| ACGIH / TWA | : | 8-hour, time-weighted average |
| NIOSH REL / TWA | : | Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek |
| OSHA P0 / TWA | : | 8-hour time weighted average |
| OSHA Z-1 / TWA | : | 8-hour time weighted average |

AIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECS - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable

SAFETY DATA SHEET

EASTMAN

according to the OSHA Hazard Communication Standard

Skydrol® PE-5

PRD / SDSUS / Z8 / 0001

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/13/2026 |
| 3.4 | 05/13/2026 | 150000093410 | Date of first issue: 09/06/2016 |

Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 05/13/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8